









Product Picture	Product Name	Product Code	Description
	Multi Card Reader	Xylia0001	A USB 2-in-1 card reader is a compact adapter that allows reading two types of memory cards (e.g., SD and microSD) through a single USB connection. It provides plug-and-play convenience for transferring data between cards and computers or mobile devices.
	TB-1505 Terminal Strip Connector	Xylia0002	The TB-1505 is a 15A/600V fixed terminal block with 5 poles. Supporting wire sections of 0.5-1.5mm <sup>2</sup> , widely used in electrical and industrial applications. Its compact dimensions (63×22×17mm) and reliable plate-type connection ensure secure transitions in circuits.
	TB-2506 Terminal Strip Shorting Bar	Xylia0003	TB-2506 is a 6P terminal block with 25A and 600V. Designed for wire cross-sections of 0.5-2.5mm <sup>2</sup> . It is widely used in electrical and industrial applications. It features a fixed design suitable for appliances, machinery.
	SV1.25-3 Fork Terminal Insulated	Xylia0004	SV1.25-3 is a fork-type insulated crimp terminal made of tinned copper (T3/H62). It is designed for cold-pressing applications in industries like machinery, automotive, and aerospace, with threaded inner holes for secure wire connection.
	Male to Female SMA Connecting cable	Xylia0005	It is a high-frequency coaxial cable assembly with threaded coupling. It is widely used in wireless communication, radar, and test equipment.
	3dBi Foldable SMA Antenna	Xylia0006	It is a compact omnidirectional WiFi antenna with SMA connectors. It is usually used in routers and wireless devices for stable signal transmission.
	868MHz Helical Antenna Straight	Xylia0007	It is a compact omnidirectional helical coil antenna made of phosphor bronze, widely used in IoT and smart home devices.

	Single Core Hook-Up Wire 22AWG	Xylia0008	PVC-insulated hook-up wire with 300V/80°C rating, featuring VW-1 flame resistance. And AWG 32-16 tinned/bare copper conductors, primarily used for internal wiring in appliances, electronics, and medical devices
	Brass Nut Insert	Xylia0009	A brass threaded insert with double-helical knurls, designed for plastic molding applications (M2-M5 sizes) to create durable threaded connections in plastic components.
	YF-S301 Flow Sensor	Xylia0010	A compact turbine-type flow meter with a measurement range of 0.3-10L/min and low startup flow (<0.3L/min), designed for liquid monitoring in industrial and household applications.
	Anti-Static Shielding Bag	Xylia0011	It is a specialized packaging solution featuring a metalized (aluminum) layer to block external static electricity, commonly used for protecting sensitive electronic components from ESD damage. And there are many sizes to choose from.
	MKA-14103 Reed Switch	Xylia0012	A standard open-type magnetic switch with a glass tube length of 14.2mm and total length of 44.7mm. It features a gold-plated contact, operates within -55°C to 125°C.
	Solar Panel 5V 500mA	Xylia0013	Made primarily of silicon-based cells, it offers an eco-friendly power solution for off-grid systems while maintaining efficient energy conversion under direct sunlight.
	RX012 4 Channel Receiver	Xylia0014	Designed for industrial/consumer applications like alarm systems and appliance remotes.

 <p>5.5*2.1 3.5*1.3</p>	DC power plug	Xylia0015	<p>It is a standardized connector with various size specifications (e.g., 5.5×2.1mm, 3.5×1.35mm) for transmitting DC power.</p> <p>Supporting different current capacities based on diameter.</p>
--	---------------	-----------	---