

Product Picture	Product Name	Product Code	Description
	REX-C100 Temperature Controller	Enya0016	Power : 250V10A Detective temperature range : 0-400-1372° Heat-reset proportional cycle: 1~100 sec Dimensions:48 x 48 x 110 (mm) ±0.2mm
	MDR-60 Single Output Rail Switching Power Supply	Enya0017	Voltage : 5V / 12V / 24V / 48V Power : 50W/ 60W Input Voltage : 85~264VAC 120~370VDC
	MDS100A Three Phase Rectifier Bridge module	Enya0018	Maximum Current: 100A Maximum Voltage: 1600V Number of Phases: 3 Phases Material: ABS+Metal
	Chassi robot war tank model	Enya0019	Motors : 130 Voltage : 6-8V Power by: 4x AA batteries (not included) Size: 9.7cm*18.5cm*5cm Good damping effect, you can press down to 0.7cm
	125KHz RFID Access Control Keypad Machine	Enya0020	User Capacity : 1000 user cards Working Frequency : 125KHz Working Current : <100mA Working Voltage : DC12 Reading Distance : 2-10cm
	JDM11-6H 6 Digit Electronic Counter Display	Enya0021	Supply voltage : 12-24VAC/DC; 100-240VAC; 36, 380 VAC Counting range : 1-999999 Power consumption : 3VA max Insulation resistance : 100MΩ min. at 500 VDC
	MAKEY MAKEY DELUXE KIT WITH CABLES	Enya0022	Voltage : Type C input 5V Current: 500mA Main IC: ATMEGA32U4 This allows you to connect all types of funny things as input.
	MEC26 multi-coin comparator electronic coin changer	Enya0023	Current : 50mA Power supply : DC12V±10% Uses : used in arcade game machines, vending machines, message chairs, etc.
	USB DIGITAL MICROSCOPE 2.0MP 1000X	Enya0024	Magnification : 1000X Material : ABS + electronic components Mini Pocket Microscope : Lightweight and portable, portable microscopes's convenient for travel and exploration.
	Aluminum heatsink for SSR solid state Relay	Enya0025	Suitable for 10-40A
	21 in 1 Wire Stripping Pliers	Enya0026	Total length : 185mm Width : 5.6cm Suitable for thin cables, stripping, cutting, etc. Material: Stainless steel
	GC-01 Nuclear radiation detector	Enya0027	Radiation dose rate ranges : 0.01µSv/h-1000µSv/h Ray Detection : X, γ and β rays Item size : 120 * 78 * 27mm Material: ABS+silicone
	Dt2234C + Digital Tachometer Meter Tester	Enya0028	Test range : 2.5RPM ~ 99,999RPM(RPM) Sampling time : 0.8 seconds (above 60 RPM) Time base : 6MHz quartz crystal oscillator Range selection : Automatic switching Power consumption : about 35mA
	Hackrf one portapack H2 SDR Radio Assembled	Enya0029	MAX2837 is replaced by MAX2839 Working frequency : 1mhz~6ghz 3.2-inch 240*320 TFT screen 4-layer gold plate; DC 2.1 interface
	RW1990 Rewritable iButton Card	Enya0030	Serial Number : Global 64-bit numbers only System logic: 64-bit contact protection Memory : 8 KB RAM Operating Temperature : -40~85 Waterproof