


Product Picture	Product Name	Product Code	Description
	DIY Joystick Console Kit	Vicky0106	Mounting hole diameter:28-30mm Connection:USB 2.0 wired Compatibility:Desktops and laptops Installation:Simple wiring and easy setup
	OF06ZAT G3/4 Water Flow Sensor	Vicky0107	Frequency:F=1.2*Q (L/min) Flow range:30-3000 L/h Humidity range:35%-90% RH Current:≤10mA(DC 5V) Allowable pressure resistance:≤1.0MPa
	6 LED Touch Dimmable Night Light	Vicky0108	200mA current,1W ultra-low power Color temperature:white light (5500K);yellow light:3200K Environmentally friendly,lead-free process,harmless to the human body It boasts an ultra-thin,bright,and durable LCD display with an LED backlight,which is safe for the eyes
	10X Round Magnifying Glass	Vicky0109	Material:Optical glass lens Dimensions:52*47*42mm Applications:Jade,jewelry,integrated circuits,textiles
 ESP32 WIFI LVGL With 2.8 Touch TFT	ESP32 2.8-inch TFT Module with Touch	Vicky0110	Size:50*86mm App-based remote control,remote environmental data collection,and data fusion The ESP32 development board is based on the ESP32-D0WDQ6 controller,a dual-core CPU with a clock frequency of up to 240MHz
	Lithium Battery Explosion-proof Bag	Vicky0111	Colour:Grey,black Size:18*23cm/23*30cm 18*23cm for batteries under 10,000mAh 23*30cm for batteries over 10,000mAh Each side is reinforced with double nylon thread
	4.5V 2/4-minute DIY Recorder	Vicky0112	Powerful recording capabilities,up to 2/4 minutes of continuous recording Built-in power-off save function ensures recorded content is retained even in a power outage Suitable for recording toys,gift boxes,and advertisements

	Shell LED Flow Light Kit	Vicky0113	PCB Material:Double-Sided FR-4 1.6mm Operating Voltage:DC3V (1 CR1220 button battery) Lighting Speed:6 settings:1000ms,500ms,100ms,50ms,20ms,10ms
	Aluminum Shell CP2102 USB to TTL UART Module	Vicky0114	Supports STC full range microcontroller burning for 3.3V and 5V Shell material:Aluminum shell
	SK150S Buck-boost Power Supply Module	Vicky0115	Packaging size:104*70*52mm MPPT function:Supports MPPT solar charging Output voltage:0-40V Screen size:1.8 inches
	VC17B+ Digital Multimeter	Vicky0116	DC voltage:0.1V-1000V AC voltage:0.1V-750V Capacitor:0.1mF~10nF Frequency:0.1Hz~999.9Hz Automatic range,intelligent anti burn,shock and anti drop,high-definition backlit display screen
	G22060HA1BL AC115V Axial Fan	Vicky0117	Rated voltage:115V 50/60Hz Rated currents of 0.42A/0.46A are available Size:222*222*60mm Bearing type:Ball bearing
	9V 2A Charger	Vicky0118	Input voltage:AC100-240V,50-60Hz Interface:UK,US,AU Cable length:1m Interface:5.5*2.5mm/5.5*2.1mm
	4mm Nickel Plated Universal Rotating Hose	Vicky0119	Customized products Material:nickel-plated iron We can customize product length according to customer needs

	Waterproof TYPE-C Female Socket Buckle	Vicky0120	Colour:Black/White/Transparent Regular line length is 15cm Support customization:line length and number of lines
---	--	-----------	--