
















Product Picture	Product Name	Product Code	Description
	SN-28B Crimping Pliers	Karlie121	Applicable terminals: TAB 2.8, 4.8 terminals Compression capacity: 0.1 - 1mm ² US standard AWG: 27-17AWG length: 190mm Weight: 0.37kg
	D1 Automatic Crimping Pliers	Karlie122	Wire stripping range: AWG10-24 / 0.2-6mm ² Compression Terminals: AWG22-4 / 0.5-6mm ²
	7-inch Duckbill Crimping Pliers	Karlie123	Wire core cross-sectional area Single strand wire stripping range: 0.2-3.3mm ² Multi-strand wire stripping range: 0.2-6.0mm ² Cable stripping range: 0.2-0.5mm ² Thread trimming range Single strand wire stripping range: 0.08-2.0mm ² Multi-strand wire stripping range: 0.09-3.5mm ² Cable stripping range: 8mm (Max)
	SLT-5021 Crimping Pliers	Karlie124	Wire stripping range Wire diameter: 0.6, 0.8, 1.0, 1.3, 1.5, 2.0, 2.5MM US standard AWG: 22, 20, 18, 16, 14, 12, 10
	JX-1301 Crimping Pliers	Karlie125	Cut and strip 10-24 AWG copper or aluminum wire, solid or stranded Crimp 10-22 AWG insulated terminals Crimp 4-22 AWG non-insulated terminals Crimp 7-8 mm ignition terminals
	BST-5022 Crimping Pliers	Karlie126	Wire stripping range: 0.5-1.6mm ² Weight: 157g
	BST-1041 Crimping Pliers	Karlie127	Wire stripping range: 0.9-5.5mm ² Weight: 147g

	DL2606 Crimping Pliers	Karlie128	Wire stripping range: 0.8-2.6mm Crimping range: 0.6 ² -4 ² mm
	81 in 1 Screwdriver Kit	Karlie129	56Bits in the following sizes: Flathead Size: 1.0mm , 1.3mm , 1.5mm , 2.0mm , 2.5mm , 3.0mm , 3.5mm , 4.0 mm Hex Size: 0.7mm , 0.9mm , 1.0mm , 1.3mm , 1.5mm , 2.0mm , 2.5mm , 3.0mm , 3.5mm , 4.0mm Phillips Size: PH000, PH00, PH0, PH1, PH2 Torx Security: TR8, TR9, TR10, TR15, TR20 (Compatible with Non-Security) Triangle Size: 2.0mm , 2.3mm Tri-point Size: 2.0mm , 3.0mm Pentalobe Size: 0.8mm , 1.2mm Square Size: SQ0, SQ1 Torx Size: T3, T4, T5, T6, T7 Pozidriv: PZ000, PZ00, PZ0, PZ1, PZ2 Nut Driver Sizes: 2.5mm , 3.0mm , 3.5mm , 4.0mm , 4.5mm , 5mm Spanner Size: 2.6mm SIM Eject Bit: 1mm Y-tip Sizes: 0.6mm (For iPhone 7/7plus/8/8P/X) Special Phillips Size: 1.5mm for remove the iPhone middle plate's screws
	JM-Y03 PLUS Screwdriver Kit	Karlie130	Rated Voltage: 3.7v Frequency: 395 r/min Max. Torque: 1200 MAH Dimensions: 240*104*35 mm Weight: 0.47kg
	25 In 1 Screwdriver Kit	Karlie131	Rated Voltage: 3.6v 24 precision bit models, suitable for mainstream electronic products and new small household appliances disassembly and assembly needs 0.05N-m* can be used for precision objects such as mobile phones, watches, and glasses. 0.2N-m* can be used in smart speakers, notebooks and other electronic products
	9 In 1 Tweezers	Karlie132	Tweezers model: ESD-10 ESD-11 ESD-12 ESD-13 ESD-14 ESD-15 ESD-17 ESD-17 ESD-34A Usage: Precision tweezers are ideal for beading, other fine crafts, medical treatment, laboratory work, beauty hair removal, and many aspects of watch and clock repair
	Screw Magnetic Working Pad	Karlie133	Product dimensions: 14.5×8.9CM Thickness: 0.8MM Net weight of products: 27.2g Scope of application: Apple mobile phone/laptop repair

	Repairing Heat Insulation Pads	Karlie134	High temperature resistant material about 500°C Soft and no deformation Chip motherboard slot Small screw positioning grid Screw driver fixing groove There are many sizes you can choose
	6 In 1 Repair Welding Kit	Karlie135	Applications: For soldering, assembly, and repair of printed circuit boards (PCB).